

# The SED Machine - Fast classification of transient objects

Andreas Ritter<sup>1</sup>, N. Konidaris<sup>2</sup>, C. C. Ngeow<sup>1</sup>, R. Quimby<sup>3</sup>  
and S. Ben-Ami<sup>4</sup>

<sup>1</sup>Graduate Department of Astronomy, National Central University,  
email: [azuri.ritter@gmail.com](mailto:azuri.ritter@gmail.com)

<sup>2</sup>California Institute of Technology, CA, USA <sup>3</sup>University of Tokyo, Japan <sup>4</sup>The Weizmann  
Institute of Science, Israel

**Abstract.** The field of time-domain astronomy is expected to enjoy a golden age during this decade. However, the traditional method for the classification of transient candidates using spectra obtained with medium- to large-aperture telescopes is extremely time consuming and struggling to keep up with the discovery rate. The Spectral Energy Distribution (SED) Machine uses a new approach in order to overcome this shortcoming.

**Keywords.** instrumentation: spectrographs, techniques: photometric, techniques: spectroscopic, telescopes, stars: novae, gamma rays: bursts

---

The Palomar Transient Factory (PTF, Law 2009, Rau 2009) is currently discovering  $\sim 4,000$  candidate transients per year. Traditionally these transient candidates are classified spectroscopically using medium to large aperture telescopes. Even with a relatively large amount of telescope time, only about 10% of the transient candidates can be followed-up and classified. In order to overcome this shortcoming for PTF and other future large-scale transient surveys, a new approach is needed.

The SED Machine (Ben-Ami 2012) was specifically designed to classify transients at a high rate using small-aperture (1-2 m) telescopes. Spectra taken at a resolution of  $R \sim 100$  contain as much information for classification as  $R \sim 1,000$  spectra, but with an increase in signal-to-noise per second of a factor of 3. This means that the SED Machine is sufficient to classify transients at a high success rate using small-aperture telescopes.

The SED Machine hosts a 4-colour Rainbow Camera (RC) for target acquisition and flux calibration, as well as the IFU for the spectroscopic analysis of the transient candidates. The IFU utilises a triple prism for a nearly constant resolution of about  $R \sim 100$  in order to efficiently classifying the transient object. 3,600 hexagonal lenslets, each covering  $\sim 0.675''$  on the sky, deliver spectra of the target, the host galaxy, and the sky background. The RC is a photometric subsystem taking images at 4 bands simultaneously: Sloan  $u$ ,  $g$ ,  $r$ , and  $i$ . The comparison of the reduced photometric images to high-quality photometric catalogues will allow for the correction of the simultaneously acquired spectra for atmospheric extinction, seeing variations, and other time dependent factors that affect the system transmittance.

The Data-Reduction Pipeline (DRP) for the IFU is based on the STELLA DRP (Ritter & Washuettl, 2004). It includes the standard data-reduction steps such as bad-pixel correction, overscan and Bias subtraction, Flat-fielding, and wavelength calibration. New instrument-specific procedures have been developed for spectra tracing, scattered-light subtraction, optimal extraction (Ritter *et al.*, *subm.*), and sky subtraction of the spectra (Ritter *et al.*, in prep.).