

researchers annealed the samples in 1 atm flowing oxygen at 900°C. Following the implantation with one, two, and then all of the elements, secondary ion mass spectrometry depth profiles were taken of both the annealed and unannealed samples. The researchers found that when magnesium was implanted on its own, it did not diffuse after annealing. They also found that the magnesium moved most when it was co-implanted with just sodium, and less when aluminum was also implanted. The researchers said, "These findings corroborate the roles of sodium, magnesium, and aluminum in the oxidation behavior of NBD 200 silicon nitride ceramic."

PAMELA JOHNSON

Protein Promotes Nucleation in Water Microdroplets

Ice crystallization in micro-sized water droplets plays an important role in nature. Researchers at the National University of Singapore have made a quantitative measurement of the interfacial effect of impurities on ice nucleation kinetics. Using microdroplet suspension to minimize the effects of the container and foreign particles, Du Ning and X.Y. Liu found that the protein lysozyme promotes freezing as a result of its effects on the interfacial kinetics of nucleation. The crystallization of microdroplets has significant implications for natural processes or systems such as climatic systems and the freezing and antifreezing processes within plants and animals.

As described in the July 15 issue of *Applied Physics Letters*, a 0.4- μ l droplet of deionized water was suspended between two layers of oil of different densities. To study the nucleation kinetics, the researchers measured the amount of time it took for an observable amount of the new phase to appear at several different temperatures. This induction time included both the time for crystals to nucleate and the time for them to grow to an observable size. However, because ice crystals grow much faster than they nucleate, the growth time can be neglected, and the time measured in the experiment was considered to be the nucleation time only.

At a constant nucleation rate, a smaller water droplet has a longer induction time. In bulk water, a small change in volume during the experiment has a negligible effect, since the total volume is so large. However, for microdroplets, the change in volume can double the induction time. The researchers included the size effects by multiplying the induction time by the volume of the water droplet, allowing a precise and reproducible measurement of the nucleation kinetics. The effects of pro-

teins on ice nucleation kinetics was also studied. The researchers found that the addition of lysozyme at 0.05 wt% to the droplets had two effects. First, it raised the energy barrier for removing impurity molecules from the surface, which inhibited nucleation. Second, the lysozyme decreased the interfacial free energy. This made the nucleation time increase less rapidly with the supercooling temperature and promoted nucleation. Because this latter effect is dominant, the net effect of the lysozyme is to promote nucleation.

ELIZABETH A. SHACK

Possibility of the Formation of Mesostructured Silica Titania Mixed-Oxide Thin Films with High Titania Load Demonstrated

The ability to prepare mesostructured thin films is a prerequisite to the implementation of many technological applications such as sensors, catalysts, and microelectronics. A group of researchers at the Institute of Materials Chemistry within the Vienna University of Technology, Austria, and the Advanced Materials Laboratory at the University of New Mexico has developed a method for the morphology-controlled synthesis of mesostructured silica titania mixed-oxide thin films with a high titanium load (Si:Ti ratio as high as 5:1) and good distribution of titanium atoms in the silica pore wall.

As reported in the June 17 issue of *Chemistry of Materials*, Nicola Hüsing of Vienna and co-workers used a titanium-coordinated surfactant as a structure-directing agent in their rapid and continuous technique for the formation of mesoporous silica titania mixed-metal-oxide thin films. The underlying principle is based on the evaporation-induced self-assembly of a modified amphiphile in combination with simultaneous sol-gel processing of the inorganic species. The researchers used the hydrophilic head group of oligo(ethylene oxide) alkyl ether surfactants {Brij56 [C₁₆H₃₃(OCH₂CH₂)₁₀OH]/Brij92 [C₁₈H₃₅(OCH₂CH₂)₂OH]} for coordination to the titanium alkoxide. The thus-modified surfactant performs two essential functions, acting as both a structure-directing agent and a coordinating ligand to lower the reactivity of the titanium alkoxide.

Deposition of the thin films was performed by a dip-coating method from the sol. After calcination at 450°C for 3 h, transparent, crack-free, and optically uniform silica titania films with a thickness of 200–250 nm were obtained. The researchers confirmed a well-defined, ordered structure and a good distribution of tetrahedrally coordinated titanium

atoms in the silica pore walls by low-angle x-ray diffraction, transmission electron microscopy, and UV- and Fourier transform infrared spectroscopy.

The researchers examined the thermal stability of the films in the temperature range of 450–1000°C. After annealing at temperatures above 450°C, amorphous titania converts to anatase and, later on (at 800°C), to rutile. The research team concluded that the proposed approach opens the way to a variety of mesostructured mixed metal oxides.

ANDREI A. ELISEEV

Spontaneous Emission from CdSe/CdS Core-Shell Quantum Dots Modified in the Presence of a SiO₂/Si Interface

The ability to precisely control the optical and electronic properties of nanomaterials by simply changing their size has led to potential application of these materials in areas such as biological chips, solar-energy conversion, catalysis, and light-emitting diodes. The desire for greater understanding of the properties of these unique materials has spawned further research. A group of researchers led by Min Xiao in the Department of Physics at the University of Arkansas has demonstrated a method to control the photoluminescence (PL) intensity of CdSe nanocrystals by adjusting their position with respect to a SiO₂/Si interface. They studied the spontaneous-emission lifetime of CdSe/CdS core-shell quantum dots as a function of distance between the dots and a polished Si surface. The researchers observed a damped oscillatory behavior in the lifetime of the PL as the separation distance between the nanomaterials and the surface was increased. According to Xiao, "Control of spontaneous emission from semiconductor structures may be useful in future applications of optoelectronic devices."

As described in the July 15 issue of *Optics Letters*, the researchers used CdSe nanocrystals, 4 nm in diameter and passivated with a CdS shell, to increase the PL efficiency of the materials. The nanomaterials were added to a solution of poly(methyl methacrylate) and spin-coated onto a layer of SiO₂ thermally grown on a silicon wafer. The thickness of the SiO₂ layers was varied between 20 nm and 400 nm. The researchers then excited the CdSe film with 400-nm laser radiation and measured the PL intensity decay at 605 nm through the use of a time-correlated photon counting system.

The researchers found that the spontaneous-emission lifetime showed a damped oscillatory dependence on the separation distance between the nano-

material film and the SiO₂/Si interface. The researchers said that the interface causes this behavior in two ways. First, the interface reflects some of the PL radiation, producing constructive and destructive interference between the directly emitted and reflected radiation. The PL intensity increases (and lifetime decreases) for samples in which the thickness of the SiO₂ layer allows mostly constructive interference. The opposite is true when destructive interference predominates. Second, the interface causes a damped oscillatory fluctuation in the local density of the optical modes that, in turn, has the same effect on the PL intensity and lifetime. This semiconductor-interface-induced optical-mode density fluctuation has been predicted by quantum mechanical calculations and previously observed for single-atom emitters.

GREG KHITROV

Single-Phase Ba₂Ti₉O₂₀ Fabricated after Addition of 5% B₂O₃

The compound Ba₂Ti₉O₂₀ is known for its good microwave properties, including a high-dielectric constant. Synthesis of Ba₂Ti₉O₂₀ by solid-state reaction is a challenging procedure because of the likelihood of the formation of intermediate stable compounds and of decomposition in different phases. Different techniques have been developed to obtain single-phase Ba₂Ti₉O₂₀, including the use of solid-state additives, chemical methods such as sol-gel fabrication, and the addition of precursors. Among other additives, B₂O₃, known for improving dielectric properties and optimizing sintering conditions in other materials, is a common addition in electronic glass applications. For these reasons, it was chosen by a group of scientists from the National Taipei University of Technology and the National Taiwan Ocean University as a solid-state additive in the fabrication of Ba₂Ti₉O₂₀, as they described in the June issue of the *Journal of the American Ceramic Society*.

S.-F. Wang of Taipei and co-workers started the fabrication of Ba₂Ti₉O₂₀ from powders of 81.8% TiO₂ and 18.2% BaO. After mixing in methyl alcohol for 6 h, the powders were dried and then calcined at 1000°C for 8 h. At this point, x-ray diffraction (XRD) analysis detected two phases: BaTi₄O₉ and BaTi₅O₁₁. Powders were then mixed again with different additions of B₂O₃ in methyl alcohol for 8 h. Further mixing with 3.5 wt% of a 15% poly(vinyl alcohol) solution allowed the fabrication of disks that were later sintered at different temperatures for 6 h. A liquid-displacement method permitted the measurement

of the density of the resulting materials. Powders with 5% addition of B₂O₃ showed a higher density after sintering at temperatures below 1100°C, as compared with the material without additive.

Results after differential thermal analysis show that the material with 5% B₂O₃ has an endothermic peak at 840°C. At this temperature, B₂O₃ forms a liquid eutectic that enhances the densification process. At temperatures higher than 1100°C, evaporation of B₂O₃ precludes the increasing densification, as compared with the material without B₂O₃ addition. Comparing results from XRD analysis, the material without B₂O₃ addition revealed the presence of BaTi₄O₉ and Ba₂Ti₉O₂₀. In the case of the material with 5% B₂O₃, only Ba₂Ti₉O₂₀ was detected after sintering at temperatures as low as 900°C.

For additions of up to 10% B₂O₃, XRD revealed the formation of BaTi(BO₃)₂ and TiO₂ after sintering at temperatures below 1200°C. At higher temperatures, BaTi(BO₃)₂ decomposed and its product BaTiO₃ combined with TiO₂ to form Ba₂Ti₉O₂₀.

SIARI S. SOSA

Low-Temperature 2D-to-3D Transition in Layered Metals Correlates with the Presence of Coherent Quasi-Particles within the Layers

The transition between metal and insulator is of particular interest when materials with reduced dimensionality exhibit two- or one-dimensional characters within a three-dimensional system. Using electronic-transport measurements and angle-resolved photoemission, researchers at Brookhaven National Laboratory, the University of Connecticut, Princeton University, and Osaka University have explored the behavior of 2D metals that change to 3D materials at low temperature and proposed new means for understanding this behavior. Their findings were described in the June 6, 2002, issue of *Nature*.

In their letter, T. Valla and co-workers suggest that the crossover from full to reduced dimensionality is correlated with the presence or absence of coherent quasi-particles within the layers of the material. The researchers studied the layered metallic materials (Bi_{0.5}Pb_{0.5})Ba₃Co₂O₇ and NaCo₂O₄ that become effectively 3D materials at low temperatures, below the crossover temperature of ~100–200 K.

The technique of angle-resolved photoelectron spectroscopy (ARPES) employed in this study has the advantage of directly measuring the single-particle spectral function that appears in the equation describing conductivity. It also is able to

investigate deeper states, unlike transport probes, which may be crucial to understanding higher-temperature behavior. Valla and co-workers observed a dramatic correlation between dimensionality crossover and measured features of the spectral function measured by ARPES. A sharp quasi-particle peak is apparent in the low temperature 3D state and broadens and disappears as the temperature increases and the system becomes effectively 2D.

Although the researchers speculate that a variety of competing mechanisms may play greater or lesser roles in effecting the crossover to the 3D ground state, the proposed importance of coherent quasi-particles provides new insight into this phenomenon. Valla said, "The existence of quasi-particles has been at the core of our understanding of transport phenomena in solid-state materials for decades and the behavior observed in this work points toward the necessity of modifying the conventional picture."

EMILY JARVIS

Exhibit Opportunities

for

Start-Up Companies

FALL MEETING



2002 MRS Fall Exhibit

December 3-5, 2002
Hynes Convention Center
Boston, MA

The **MRS Entrepreneur Program** will afford you an excellent opportunity to introduce new products or technologies to materials science/engineering professionals who walk the exhibit floor seeking technical solutions to their challenges. This program offers reduced booth rental rates to companies who meet the following criteria:

- Less than 3 years old
- Annual sales less than \$1M
- Fewer than 10 employees

To take advantage of the Entrepreneur Program or for more information on how MRS can market your company in the world of materials science, contact Mary E. Kaufold at 724-779-8312 or kaufold@mrs.org.

www.mrs.org/mo/