

March 11 issue of *Chemistry of Materials*, Y. Shirota and co-workers from Osaka University in Japan reported the synthesis and properties of a novel class of high-performance, color-tunable emitting amorphous molecular materials with bipolar characters: 4-dimesitylboryl-N,N-bis(9,9-dimethylfluoren-2-yl)aniline (FIAMB-0T); 2-[4-[bis-(9,9-dimethylfluoren-2-yl)amino]phenyl]-5-(dimesitylboryl)thiophene (FIAMB-1T); 2-[4-[bis-(9,9-dimethylfluoren-2-yl)amino]phenyl]-2'-dimesitylboryl-5,5'-bithiophene (FIAMB-2T); and 5-[4-[bis(9,9-dimethylfluoren-2-yl)amino]phenyl]-5''-dimesitylboryl-2,2':5',2''-terthiophene (FIAMB-3T).

The molecular design of these materials is based on connecting both electron-donating and electron-accepting moieties (which undergo reversible oxidation and reduction) through a central  $\pi$ -conjugated system. In other words, the incorporation of the difluorenyl(phenyl)amine and dimesitylboryl moieties provide both electron-donating and electron-accepting properties, respectively, and facilitated formation of amorphous glasses due to their nonplanar molecular structures. The central thiophene rings control the highest occupied and lowest unoccupied molecu-

lar orbital energy levels, depending on the material's  $\pi$ -conjugation length. The researchers reported that emission color can be tuned by varying the conjugation length of the thiophene unit.

The researchers reported the fabrication of electroluminescent devices using FIAMB-*n*T as emitting or host materials and the development of a high-performance white-light-emitting electroluminescent device using a bilayer combination of FIAMB-0T and FIAMB-3T.

ANDREI A. ELISEEV

### Surface Properties Reversibly Switched Using Electrical Potential

A research team from the Massachusetts Institute of Technology (MIT), the University of California at Santa Barbara (UCSB), and UC—Berkeley have developed a process that dynamically changes interfacial properties by conformational transitions, or switching, of surface-confined molecules. Unlike other methods that involve chemical reactions, the team has demonstrated the ability to use an active stimulus, such as an electrical potential, to effect such changes without altering the system's environment.

As reported in the January 17 issue of *Science*, a self-assembled monolayer of (16-mercapto)hexadecanoic acid was prepared on a gold surface. This molecule was chosen because it has a hydrophobic chain and a hydrophilic group on one end; therefore, it may grant different properties to the surface, depending on which part of the molecule is exposed. In order to allow for the switching, the monolayers need to be less dense than conventional self-assembled monolayers; that is, sufficient spatial freedom must be established for each molecule. A monolayer with an optimum spacing between molecules was obtained using a precursor molecule with a globular head group. Hydrolysis of the globular group yielded a low-density monolayer of the molecule of interest.

In the equilibrium state, the molecules organized in a straight fashion on the surface, exposing their hydrophilic end. Joerg Lahann of MIT, Samir Mitragotri of UCSB, and co-workers observed that after applying an electrical potential to the gold surface, the molecules' end groups were attracted toward the charged surface, showing the hydrophilic chains. Sum frequency generation (SFG) spectroscopy was used to analyze the conformational states of the monolayer, since the intensity of the SFG spectrum is affected by the orientation of the molecules. The results show that an electrical potential changes the conformation of the molecules in the monolayer, and that the switching is a reversible process. Contact angles were measured over four switching cycles, and while a large hysteresis was observed, the drop in contact angle was also determined to be reversible. The researchers attributed the observed hysteresis to surface chemical heterogeneity and roughness.

According to the researchers, these findings have important implications for the dynamic control of macroscopic surface properties. The researchers identified applications in microfluidics, microengineering of smart templates, and microfabrication of controlled-release devices.

MARIA M. CORTALEZZI

### Stable $\alpha$ -Phase Nickel Hydroxides Obtained with 10% Aluminum Substitution

Alpha-phase nickel hydroxides have recently been investigated in order to increase the performance of rechargeable alkaline batteries. The  $\alpha$ -nickel hydroxide has a superior electrochemical capacity of 433 mAh/g theoretical and 350 mAh/g actual, as compared with  $\beta$ -nickel hydroxide at 289 mAh/g theoretical and 273



## 10th International Conference on Defects—Recognition, Imaging and Physics in Semiconductors (DRIP X)

September 29 – October 2, 2003  
Les Salines Holiday Village in Batz-sur-Mer  
(near Nantes, France)

### ANNOUNCEMENT AND CALL FOR PAPERS

The purpose of DRIP X is to provide an opportunity for scientists and engineers from both the academic sphere and industry to meet together for an efficient scientific exchange on the topics related to the different methods and techniques used for the recognition, imaging and analysis of defects in semiconductor materials and devices.

#### Conference Themes

- Nano and atomic scale defect assessment, near field probe methods
- Submicron far field optical imaging, spectroscopy
- Electrical and transport characterization
- Electron beam methods and x-ray based mapping techniques
- Defect mapping over large area wafers
- Si, III-Vs including nitrides, SiC, IV-IVs, II-VIs, organic compounds
- Strategies for comparing the results of different techniques
- *In situ* diagnostics and process control

Abstract Deadline: April 30, 2003

J.P. Landesman, Institut des Matériaux de Nantes, CNRS  
2 rue de la Houssinière, 44322 Nantes cedex 3, France • Tel: (33) 2 40 37 39 55

[www.cnrs-imm.fr/dripX/](http://www.cnrs-imm.fr/dripX/)

For more information, see <http://advertisers.mrs.org>